

Range: **MONOBLOCK**
 Type name: **OZX250-6**



		
06	-	D

PERFORMANCES*		CONFIGURATION	
Voltage:	6 V	Size:	261x181x276 mm (GC2)
Capacity:	250 Ah (100h)	Polarity:	06
Cap. 10/20h:	185/225 Ah	Terminal:	D (dual)
Energy at 100h:	1,5 kWh	Holddown:	-
Cicles at 50%:	900	Ventilation:	Individual plugs
PV Cicles (24%):	2000	Maintenance:	Low maintenance
Self-Discharge:	6 months		
<small>(from the date of production, at 25°C)</small>			

*According to standards IEC 60896/61427

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Casted flat plate	Container:	PP/black
Alloy:	Antimony	Lid:	Flat, PP/black
Separator:	PE envelope	Plugs:	Screw, PP/black
Total Weight:	30,1 kg	Handles:	(fixations on lid)
Origin:	Europe		

RECOMENDATIONS	
Storage:	Check voltage every 3 months. Avoid exposure to sub-zero temperatures.
Recharge:	Use automatic chargers with constant voltage.
Installation:	Use the appropriate cable section and length. Keep connections tight.

TABLES & CHARTS

MONOBLOCK

OZX250-6

OZX250-6 BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate	C5 (5h)	C10 (10h)	C20 (20h)	C100 (100h)
End of discharge voltage	5,10 V	5,25 V	5,25 V	5,40 V
Discharge capacity	185 Ah	215 Ah	225 Ah	250 Ah

