

Range: **MONOBLOCK**

Type name: **OZX125.0**



		
0	-	1

PERFORMANCES*		CONFIGURATION	
Voltage:	12 V	Size:	343x173x240 mm (D2)
Capacity:	125 Ah (100h)	Polarity:	0
Cap. 10/20h:	110/115 Ah	Terminal:	1 (taper)
Energy at 100h:	1,5 kWh	Holddown:	-
Cicles at 50%:	50	Ventilation:	Central
PV Cicles (24%):	200	Maintenance:	Very low maintenance
Self-Discharge:	12 months		
<small>(from the date of production, at 25°C)</small>			

*According to standards IEC 60896/61427

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Punched, with regular surface	Container:	PP/black
Alloy:	Calcium	Lid:	Flat, PP/black
Separator:	PE envelope	Plugs:	Pressure, PP/black
Total Weight:	24,4 kg	Handles:	On lid, PP/black
Origin:	Europe		

RECOMENDATIONS	
Storage:	Check voltage every 6 months. Avoid exposure to sub-zero temperatures.
Recharge:	Use automatic chargers with constant voltage.
Installation:	Use the appropriate cable section and length. Keep connections tight.

TABLES & CHARTS

MONOBLOCK

OZX125.0

OZX125.0 BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate	C5 (5h)	C10 (10h)	C20 (20h)	C100 (100h)
End of discharge voltage	10,20 V	10,50 V	10,50 V	10,80 V
Discharge capacity	95 Ah	110 Ah	115 Ah	125 Ah

