



U.S. Battery - US8VGCXC3 - Batería US de 170AH serie DEEP CYCLE

Batería de arranque para coches sin mantenimiento de 8vV . 170AH 325A.DEEP CYCLE series

Las baterías de ácido de plomo inundado de US Battery están diseñadas y probadas para proporcionar el ciclo más rápido hasta la capacidad nominal completa y tienen la energía total más alta entregada durante la vida útil de la batería.

Batería US de serie DEEP CYCLE de 170Ah para aplicaciones estacionarias y 133Ah, RC (min) 474 para aplicaciones de tracción, con terminales automotrices estándar (tipo 1) T875 y tamaño de Largo 260mm x Ancho 181mm x Alto 286mm.

DEEP CYCLE Battery Type Capacity C20h (Ah) Capacity C5h (Ah)/td> RC (min)@25A BOX
DIMENSIONS TECHNICAL CHARACTERISTICS L(mm) AN (mm) AL(mm) LAYOUT TERMINALS HOLD
DOWN 6 volt US2200XC3 232 181 474 T105 260 181 286 0 - Offset-S B0 US305XC2 310 261 715
J305 302 181 371 0 - Offset-S B0 <USL16XC2 385 297 865 L16 302 181 425 0 - Large L B0 8 volt
US8VGCXC3 170 133 325 T875 260 181 286 0 - UTL B0 12 volt US24DCXC2 85 68 145 G24 276 171
238 1 +__ - Dual B0 US27DCXC2 105 89 205 G27 324 171 238 1 +__ - Dual B0 US31DCXC2 130 99
225 G31 330 171 243 9 +__ - Dual B0 US12VRXXC3 155 122 292 T1275 355 179 289 1 +__ - UTL B0
US185HCXC2 220 172 443 J185 397 179 378 0 - __+ Offset-S B0





DISTRIBUCIONES

US 8VGCE XC2, US 8VGC XC2, US 8VGCHC XC2**DATA SHEET** Deep Cycle 8-Volt

US 8VGCE XC2

**US 8VGC XC2**
(US 8VGCI XC2 cover
option also available)

US 8VGCHC XC2

**Application:** Wherever Deep Cycle 8-volt batteries are needed.**Dimensions:** 10-1/4 (260)L x 7-1/8 (181)W x 11-1/4 (286)H**Type:** Flooded Lead Acid (FLA) non-sealed.**Case material:** Polypropylene / Heat Sealed**US 8VGCE XC2, US 8VGC XC2, US 8VGCHC XC2 - SPECIFICATIONS**

BCI Group Size	Model	1-hr Rate	2-hr Rate	5-hr Rate	6-hr Rate	10-hr Rate	20-hr Rate	48-hr Rate	72-hr Rate	100-hr Rate	Voltage	Standard Terminal Type	AMP HOURS (20 HR. RATE)	MINUTES @ 75 AMPS	MINUTES @ 56 AMPS	MINUTES @ 25 AMPS	Length	Width	Height	Wet Weight Lbs (kg)
GC8	US 8VGCE XC2	90	105	129	132	142	155	164	169	172	8	UTL	155	75	110	312	10-1/4 (260)	7-1/8 (181)	11-1/4 (286)	60 (27)
GC8	US 8VGC XC2	96	111	133	138	151	170	180	185	189	8	Molded-In UTL	170	82	118	325				62 (28)
GC8	US 8VGCHC XC2	109	124	147	152	164	183	194	199	203	8	UTL	183	95	136	365				67 (30)



NUEVO