



DISTRIBUCIONES

Intact - 12N5,5-3B - Batería Intact de 5AH serie CLASSIC

Batería de arranque para coches sin mantenimiento de 12V . 5.5AH 40A.CLASSIC series

Intact- CLASSIC Bateria con mantenimiento. Placas positivas tratadas para evitar desulfatación templanas. Mayor calidad en fabricacion de rejillas No dudes, una bateria de calidad con el mejor precio.

Batería INTACT AMG de libre mantenimiento de 6.5Ah con CCA (capacidad de arranque) de 80A, terminales automotrices estándar (tipo 1) de Largo 138mm x Ancho 61mm x Alto 131mm.

DYNAMIC Reemplaza Capacidad Dimensiones Polaridad Terminal (Ah-20h) (A-EN) L(mm) An (mm)

6N11A-1B - 13 119 83 161 -__+ Patilla CB3L-A - 3 99 57 111 -__+ Patilla CB3L-B - 3 99 57 111 -__+ Patilla CB4L-B - 4 120 70 92 -__+ Cuadrado CB5L-B 12N5-3B 5 121 61 131 -__+ Patilla 12N5,5-3B - 5,5 138 61 131 -__+ Patilla CB7-A 12N7-4A 8 137 76 134 +__- Patilla CB7L-B 12N7-3B 8 137 76 134 -__+ Patilla CB7C-A 12N7C-3D 8 130 90 114 -__+ Patilla CB9-B 12N9-4B-1 9 137 76 140 +__- Patilla CB9L-A2 - 9 137 76 140 -__+ Cuadrado CB9L-B 12N9-3B 9 137 76 140 -__+ Patilla CB10L-A2 12N10-3A 11 136 91 146 -__+ Cuadrado CB10L-B 12N10-3B 11 136 91 146 -__+ Patilla CB10L-B2 - 11 136 91 146 -__+ Cuadrado CB12A-A 12N12A-4A-1 12 135 81 161 +__- Patilla CB12A-B - 12 135 81 161 +__- Patilla CB12AL-A - 12 135 81 161 -__+ Patilla CB14-A2 - 14 135 91 167 +__- Cuadrado CB14-B2 - 14 135 91 167 +__- Cuadrado CB14L-A2 12N14-3A 14 135 91 167 -__+ Cuadrado CB14L-B2 12N14-3B 14 135 91 167 -__+ Cuadrado CB14A-A2 - 14 135 91 177 +__- Cuadrado CB16-B 12N16-4B 19 176 101 156 +__- Patilla CB16L-B - 19 176 101 156 -__+ Cuadrado HCB16A-A - 16 151 91 182 +__- Cuadrado CB16AL-A2 - 16 205 71 164 -__+ Patilla CB16B-A - 16 162 92 162 +__- Cuadrado CB16AL-A2 - 16 205 71 164 -__+ Patilla CB16B-A - 16 162 92 162 +__- Cuadrado CB16CL-B - 19 175 100 175 -__+ Cuadrado CB18L-A - 18 182 92 164 -__+ Cuadrado 51814 12Y16A-3B 18 186 81 170 -__+ Patilla C50-N18L-A 12N18-3A 20 206 91 164 -__+ Cuadrado C60-N24L-A 12N24-3 24 184 124 170 -__+ Patilla C60-N24AL-B 53030 24 184 124 170 -__+ Patilla CB30L-B - 30 165 130 176 -__+ Cuadrado C60-N30L-A - 30 187 130 170 -__+ Patilla





INTACT BATTERY-POWER



moto2 team

EXCLUSIVE PARTNER OF



BIKE POWER **SLA**

Sealed AGM battery (electrolyte held in Absorbent Glass Mat separators)


BIKE POWER **AGM**

Sealed AGM battery (electrolyte held in Absorbent Glass Mat separators)

BIKE POWER **CLASSIC**

Flooded lead-acid battery

BIKE
POWER **CLASSIC**



Flooded Lead-Acid Battery

— INTACT CLASSIC

IC 12N5,5-3B



Technical specifications

Voltage (V) 12

Capacity (Ah) 5.5 (10hr)

CCA (A/EN) 40

Length (mm) 138

Width (mm) 61

Height (mm) 131

Total Height (mm) 131

Layout 0

Terminal B1

LAYOUT

TERMINAL

