



marver

U.S. Battery - US305XC2 - Batería US de 310AH serie DEEP CYCLE

Las baterías de ácido de plomo inundado de US Battery están diseñadas y probadas para proporcionar el ciclo más rápido hasta la capacidad nominal completa y tienen la energía total más alta entregada durante la vida útil de la batería.

Batería US de serie DEEP CYCLE de 232Ah para aplicaciones estacionarias y 181Ah, RC (min) 474 para aplicaciones de tracción, con terminales automotrices estándar (tipo 1) J305 y tamaño de Largo 302mm x Ancho 181mm x Alto 371mm.

DEEP CYCLE Battery Type Capacity C20h (Ah) Capacity C5h (Ah)/td> RC (min)@25A BOX
DIMENSIONS TECHNICAL CHARACTERISTICS L(mm) AN (mm) AL(mm) LAYOUT TERMINALS HOLD
DOWN 6 volt US2200XC3 232 181 474 T105 260 181 286 0 - Offset-S B0 US305XC2 310 261 715
J305 302 181 371 0 - Offset-S B0 <USL16XC2 385 297 865 L16 302 181 425 0 - Large L B0 8 volt
US8VGCXC3 170 133 325 T875 260 181 286 0 - UTL B0 12 volt US24DCXC2 85 68 145 G24 276 171
238 1 +__- Dual B0 US27DCXC2 105 89 205 G27 324 171 238 1 +__- Dual B0 US31DCXC2 130 99
225 G31 330 171 243 9 +__- Dual B0 US12VRXXC3 155 122 292 T1275 355 179 289 1 +__- UTL B0
US185HCXC2 220 172 443 J185 397 179 378 0 - + Offset-S B0





US 305E XC2



US 305 XC2



US 305HC XC2

US 305E XC2, US 305 XC2, US 305HC XC2

DATA SHEET Deep Cycle 6 -Volt



Application: Wherever Deep Cycle 6-volt batteries are needed.

Dimensions: 11-7/8 (302)L x 7-1/8 (181)W x 14-5/8 (371)H

Type: Flooded Lead Acid (FLA) non-sealed.

Case material: Polypropylene / Heat Sealed



US 305E XC2, US 305 XC2, US 305HC XC2 - SPECIFICATIONS

BCI Group Size	Model	1-hr Rate	2-hr Rate	5-hr Rate	6-hr Rate	10-hr Rate	20-hr Rate	40-hr Rate	72-hr Rate	100-hr Rate	Voltage	Standard Terminal Type	AMP HOURS (20 HR. RATE)	MINUTES @ 75 AMPS	MINUTES @ 56 AMPS	MINUTES @ 25 AMPS	Length	Width	Height	wet Weight Lbs (kg)
902	US 305E XC2	193	214	245	252	273	290	307	315	322	6	Offset "S"	290	182	256	660	11-7/8	7-1/8	14-5/8	86 (39)
902	US 305 XC2	203	226	261	268	294	310	328	337	345	6	Offset "S"	310	195	276	715	(302)	(181)	(371)	90 (41)
902	US 305HC XC2	220	245	283	291	322	340	360	370	378	6	Offset "S"	340	215	304	790				96 (43)



NUEVO