



U.S. Battery - US12VRXXC3 - Batería US de 155AH serie DEEP CYCLE

Batería de arranque para coches sin mantenimiento de 12V . 155AH 292A.DEEP CYCLE series

Las baterías de ácido de plomo inundado de US Battery están diseñadas y probadas para proporcionar el ciclo más rápido hasta la capacidad nominal completa y tienen la energía total más alta entregada durante la vida útil de la batería.

Batería US de serie DEEP CYCLE de 155Ah para aplicaciones estacionarias y 122Ah, RC (min) 292 para aplicaciones de tracción, con terminales automotrices estándar (tipo 1)T1275 y tamaño de Largo 355mm x Ancho 179mm x Alto 289mm.

DEEP CYCLE Battery Type Capacity C20h (Ah) Capacity C5h (Ah)/td> RC (min)@25A BOX
DIMENSIONS TECHNICAL CHARACTERISTICS L(mm) AN (mm) AL(mm) LAYOUT TERMINALS HOLD
DOWN 6 volt US2200XC3 232 181 474 T105 260 181 286 0 - Offset-S B0 US305XC2 310 261 715
J305 302 181 371 0 - Offset-S B0 <USL16XC2 385 297 865 L16 302 181 425 0 - Large L B0 8 volt
US8VGCXC3 170 133 325 T875 260 181 286 0 - UTL B0 12 volt US24DCXC2 85 68 145 G24 276 171
238 1 +__ - Dual B0 US27DCXC2 105 89 205 G27 324 171 238 1 +__ - Dual B0 US31DCXC2 130 99
225 G31 330 171 243 9 +__ - Dual B0 US12VRXXC3 155 122 292 T1275 355 179 289 1 +__ - UTL B0
US185HCXC2 220 172 443 J185 397 179 378 0 - __+ Offset-S B0





DISTRIBUCIONES



US 12VXZ XC2
(cover option)

US 12V XC2
(cover option)

US 12VRX XC2

US 12VRX XC2 - DATA SHEET

Deep Cycle 12-Volt



Application: Wherever Deep Cycle 12-volt batteries are needed.

(Without Handles)

Dimensions: 13-1/8 (333)L x 7-1/16 (179)W x 11-3/8 (289)H

(With Handles)

14 (355)L x 7-1/16 (179)W x 11-3/8 (289)H

Type: Flooded Lead Acid (FLA) non-sealed.

Case material: Polypropylene / Heat Sealed



US 12VRX XC2 - SPECIFICATIONS

BCI Group Size	Model	1-hr Rate	2-hr Rate	5-hr Rate	6-hr Rate	10-hr Rate	20-hr Rate	48-hr Rate	72-hr Rate	100-hr Rate	Voltage	Standard Terminal Type	AMP HOURS (20 HR. RATE)	MINUTES @ 75 AMPS	MINUTES @ 56 AMPS	MINUTES @ 25 AMPS	Length with Handles	Width	Height	wet Weight Lbs (kg)
GC12	US 12VRX XC2	92	104	122	126	138	155	164	169	172	12	UTL	155	77	110	292	14 (355)	7-1/16 (179)	11-3/8 (289)	86 (39)



NUEVO